



[www.rapidradio.co.in](http://www.rapidradio.co.in)

## HF RFID Tag RRHFT01

### Features & Benefits

- Up to 256 Byte rewritable memory
- ISO 15693 and ISO 18000-3 compliant
- Customized tags available for different applications
- Application Family Identifier
- Fast Anti-collision

RRHFT01 is HF Tag working on 13.56 MHz frequency. They are available in different form factors depending on required range and various applications.

Tags are also available in various memories starting from 256 bits to 2048 bits. It is also available in inlay and label form

### Applications

- Supply chain management
- Product Authentication
- Library
- Asset Tracking
- Ticketing/Stored value

# Specifications

Parameter	RRHFT01
Supported Standards	ISO 15693, ISO 18000-3
Transponder IC	I-Code SLI
Operating Frequency	13.56 MHz
Transmission Principle	ASK / FSK
User Programmable Memory	Upto 2048 Bits
Data Retention	10 Years
Programming Cycles	100000
Operating Temperature	-25°C to +70°C
Storage Temperature	-40°C to +85°C
Dimensions	Available in various dimensions and shapes

“RapidRadio with its technical expertise in RFID technology and its physics focuses on designing, developing, innovating and deploying RFID hardware solutions”

RapidRadio Solutions reserves the right to make changes in the specification without notice.



**RapidRadio Solutions Pvt. Ltd.**

B-404, Satyamev-I, Opp. Gujarat High Court, S G Highway,  
Ahmedabad - 380 060 Tele/Fax : +91 79 2766 5256  
Email I: reachus@rapidradio.co.in Website : www.rapidradio.co.in

Yahoo/MSN/Skype : rapidradio\_solutions Gtalk : rapidradio  
(10:00 AM - 7:00 PM IST)