



www.rapidradio.co.in

HF RFID Integrated Reader RRHFLB03

Features & Benefits

- Read range up to 30 cm
- Multi protocol reader
- Sturdy and aesthetic design
- Integrated reader and antenna in single unit
- Low power consumption
- ISO 15693, ISO 14443A & ISO 18000:3 compliant
- Plug and Play with USB protocol
- USB self powered device

RRHFLB03 is a plug and play multi protocol RFID reader specially designed for Library Application. It is an integrated device where RFID reader and antenna are merged in a single unit. It is USB powered device.

It operate with industry standard tags at 13.56 MHz. The reader is easy to install and supports ISO 15693, ISO 14443A & 18000:03 Tags.

Applications

- Entry of new book or borrower
- Circulation of books
- Library visitors records

Specifications

Parameter	RRHFLB03
Operating Frequency	13.56 MHz
Power Supply	USB Self Powered
Power Consumption	700 mW max
Transmitting Power	200 mW approx.
Read Range*	Up to 30 cm
Antenna	Internal
Communication Interface	USB
Supported Transponders	ISO 15693,ISO 14443A & ISO18000:3
Indicators	Buzzer for power,read verification
Operating Temperature	-10°C to +70°C
Dimensions	340 X 340 X 20 mm
Weight	Approx. 3 kg.
Housing Material	Marine Grade Plywood or Similar
Color	White

* Read range depends on tag size & orientation

“RapidRadio with its technical expertise in RFID technology and its physics focuses on designing, developing, innovating and deploying RFID hardware solutions”

RapidRadio Solutions reserves the right to make changes in the specification without notice.



RapidRadio Solutions Pvt. Ltd.

B-404, Satyamev-I, Opp. Gujarat High Court, S G Highway,
Ahmedabad - 380 060 Tele/Fax : +91 79 2766 5256
Email: reachus@rapidradio.co.in Website : www.rapidradio.co.in

Skype : rapidradio_solutions Gtalk : rapidradio
(10:00 AM - 7:00 PM IST)